


VHF

Marine VHF Radiotelephone

Model: FM-8900S



MMSI : 1

DISTRESS

CH STATUS RECORD TIME : 0M04S

POWER : #16 DATE :

HIGH 03/FEB/10 10:11:12 0M01S

REGION : NO. REC TIME DATE (TOTAL : 006)

INT'L 001 : 0M04S 03/FEB/10 10:11:12

TYPE : 002 : 2M00S 04/APR/11 07:15:33

SIMP 003 : 0M03S 04/APR/11 09:20:00

STOP

PAUSE


BACK





Model: FM-8900S

- ▶ **Semi-duplex 25-Watt VHF radiotelephone with a built-in Class-A DSC and CH70 watch Receiver**
- ▶ **Fully meets GMDSS carriage requirements for SOLAS ships**
- ▶ **Meets the new ITU recommendation on digital selective calling system for use in the Maritime Mobile Service, ITU-R M.493-14**
- ▶ **Easy to read, high-contrast 4.3" bright color LCD**
- ▶ **Enhanced noise reduction and speaker for superb voice quality**
- ▶ **Quick access to CH16 key**
Press the CH16 key on the keypad to switch to radiotelephone display and select CH16 instantly
- ▶ **Easy channel selection with rotary control or direct keypad input**




- ▶ **Automatic entry of own ship position and time through the interfaced GPS receiver**
- ▶ **ATIS signal transmission available for inland waterways**
- ▶ **Connect to an office or home via an existing PSTN (Public Switched Telephone Network)**

telephone 0 watch receiver

Scans all channels in the selected region and CH16

The FM-8900S scans all channels in the selected region as well as watches CH16 in alternate shift.



SCAN Display

Transmitting and receiving general/distress DSC messages

By long-pressing (3 seconds) the "DISTRESS" button, DSC distress alert can be transmitted. Also, quick entry to DSC message composition screen is available by use of "DISTRESS MSG" and "OTHER DSC MSG" buttons.

In the DSC Display, the operators can view the message log of the sent/received DSC messages.

For general DSC messages, press "OTHER DSC MSG" to enter the composition screen.




DSC Display

For DSC messages for distress alert, press "DISTRESS MSG" to enter the composition screen.

For DSC messages for DROBOSE (DSC Relay On Behalf Of Someone else), press both "DISTRESS MSG" and "OTHER DSC MSG" to enter the composition screen.


Quick access to dedicated functions in the menu operation using numeric keypad

In the menu, all tasks are assigned numbers, and the operator can access each of the menu items either by turning and pressing PUSH TO ENTER knob or simply pressing the corresponding numbers on the numeric keypad.




Replay function

The FM-8900S records the latest 120 seconds of incoming communication on the currently set channel. By simply pressing the "REPLAY" button on the numeric keypad, the last-received message will be played back on the spot.



Replay Display

Day mode and Night mode can be selected according to the lighting condition of the wheelhouse



SPECIFICATIONS

PRODUCT NAME VHF RADIOTELEPHONE

GENERAL CHARACTERISTICS

Rules and Regulations	
VHF Radiotelephone	EN 301 925 V1.4.1 (2013-05)
VHF ATIS	EN 300 698-1 V1.4.1 (2009-12)
DSC	ITU-R M.493-14 (09/2015)
	ITU-R M.541-10 (10/2015)
	ITU-R M.689-3 (03/2012)
	EN 300 338-1 V1.4.1 (2017-02)
	EN 300 338-2 V1.4.1 (2017-02)
Class of emission	G3E/F3E (Radiotelephone), G2B/F2B (DSC)
Communication system	Simplex/Semi-duplex
Channels	INTL: 59 (ITU-R RR AP18(WRC-15))
	USA: 50 (FCC 47 CFR Ch. 1 § 80.371, § 80.373)
	Canada: 57 (Industry CANADA RBR-2)
	Weather: 10 (USA and Canada, receive only)
	Inland waterway: 57 (ETSI EN 300 698-1 V1.4.1 2009-12)
	Private: 20 (permitted by administrations)
Display	MEMORY CH: 50
Display	4.3 inches WQVGA (480x272 dots), color dot matrix LCD

TRANSMITTER

Frequency range	155.000 - 161.600 MHz
RF output power	High: Max 25 W, Low: Not exceed 1 W US version: Manual override for 25 W available on CH13, CH67 and CH77 (usually not exceed 1W)
Frequency stability	Less than ±1.5 kHz
TX timeout (for US & Inland-waterway)	Deactivates the transmitter after an uninterrupted transmission of more than 5 minutes
ATIS	An ATIS signal is transmitted at the end of transmission, by modulating the carrier at 1,300 and 2,100 Hz

RECEIVER

Frequency range	Simplex: 155.000 - 161.600 MHz Semi-duplex: 159.600 - 164.200 MHz
Receiving system	Double-conversion super-heterodyne 1st IF: 51.1375 MHz 2nd IF: 62.5 kHz
Sensitivity	Less than 6 dB µV at SINAD 20 dB
Adjacent channel selectivity	70 dB or more
AF output power	Built-in speaker: 3 W (4 ohms. THD 10 % or less) Handset earphone receiver: 2 mW (150 ohms)
Audio response	De-emphasis of 6 dB/oct +1/-3 dB

DSC SECTION

Message log	Receive: 50 distress messages and 50 non-distress messages Transmit: 50 messages	
Interface	Nav data: IEC61162-1 Ed.4 Printer: Centronics-compatible	
Alarm	Audible and visual on receipt of a DSC call	
DSC watch-keeping receiver	Receiving frequency	156.525 MHz (CH70)
	Sensitivity	Symbol error rate: Less than 1 % (at 0 dB µV)

POWER SUPPLY

24 VDC, Standby: 1.3 A max., RX: 2.3 A max., TX: 4.7 A max.


ENVIRONMENT

Temperature	-15°C to +55°C
Relative humidity	93% (at 40°C)
Waterproofing	
FM-8900S (VHF Radiotelephone)	IP20 (IP22 with option)
HS-2003 (Handset)	IP24
IF-8900 (Junction box)	IP22 (Bulkhead), IP20 (Tabletop)
RB-8900 (Remote station)	IP22
RB-8900-W (Watertight remote station)	IP56
RC-8900 (VHF console)	IP20

EQUIPMENT LIST

Standard		
VHF Radiotelephone	FM-8900S	1unit
Handset	HS-2003	1unit
Handset Cradle	FP05-05510	1unit
Installation materials and spare parts		1set
Option		
Junction Box	IF-8900	
Remote Station	RB-8900	
Watertight Remote Station	RB-8900-W	
Handset and Cradle		
Flush Mount Kit	OP05-129	
External Loudspeaker	SEM-21Q	
Printer	PP-8800A/PP-520	
Printer Interface Unit	IF-8500	
AC/DC Power Supply Unit	PR-241	
VHF Console	RC-8900	



INTERCONNECTION DIAGRAM



Transceiver Unit (Flushmount)

FM-8900S


4.2 kg 9.3 lb



Remote Station

RB-8900


0.7 kg 1.5 lb



Handset

HS-2003

0.2 kg 0.4 lb



Beware of similar products

All brand and product names are registered trademarks, trademarks or service marks of their respective holders.

SPECIFICATIONS SUBJECT TO CHANGE WITHOUT NOTICE

FURUNO ELECTRIC CO., LTD.
Japan | www.furuno.com
FURUNO U.S.A., INC.
U.S.A. | www.furunousa.com
FURUNO PANAMA S.A.
Republic of Panama | www.furuno.com.pa
FURUNO (UK) LIMITED
U.K. | www.furuno.co.uk
FURUNO NORGE A/S
Norway | www.furuno.no

FURUNO DANMARK A/S
Denmark | www.furuno.dk
FURUNO SVERIGE AB
Sweden | www.furuno.se
FURUNO FINLAND OY
Finland | www.furuno.fi
FURUNO POLSKA Sp. Z o.o.
Poland | www.furuno.pl
FURUNO DEUTSCHLAND GmbH
Germany | www.furuno.de

FURUNO FRANCE S.A.S.
France | www.furuno.fr
FURUNO ESPAÑA S.A.
Spain | www.furuno.es
FURUNO ITALIA S.R.L.
Italy | www.furuno.it
FURUNO HELLAS S.A.
Greece | www.furuno.gr
FURUNO (CYPRUS) LTD
Cyprus | www.furuno.com.cy

FURUNO EURUS LLC
Russian Federation | www.furuno.ru
FURUNO SHANGHAI CO., LTD.
China | www.furuno.com/cn
FURUNO CHINA CO., LTD.
Hong Kong | www.furuno.com/cn
FURUNO KOREA CO., LTD
Korea
FURUNO SINGAPORE
Singapore | www.furuno.sg

PT FURUNO ELECTRIC INDONESIA
Indonesia | www.furuno.id
FURUNO ELECTRIC (MALAYSIA) SND. BHD.
Malaysia | www.furuno.my

F-2103LB
Catalogue No. CA000001499